PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty) REC'D 0 4 NOV 2005

(PCT Article 36 and Rule 70)

WIPO PCT

1		gent's file reference	FOR FURTHER AC	TION	-		
17606.7-D2646-54-ne			FOR FUNITIES AC	HOIN	See Form PCT/IPEA/416		
			International filing date (day/month/year)	Priority date (day/month/year)		
			30.07.2004		31.07.2003		
International Patent Classification (IPC) or national classification and IPC							
H04L29/06, H04W31/04, H04Q7/38							
·							
Applicant							
T-MOBILE DEUTSCHLAND GMBH et al.							
1.	1. This report is the international preliminary examination report, established by this International Preliminary Examining						
	Authority under Article 35 and transmitted to the applicant according to Article 36.						
2.	This REPORT consists of a total of 5 sheets, including this cover sheet.						
3.	This report is also accompanied by ANNEXES, comprising: a. Some sent to the applicant and to the International Bureau) a total of 5 sheets, as follows:						
	a.⊠ s	_					
	K	and/or sheets contain Administrative Instruc	ing rectifications authori:	ngs which have been ar zed by this Authority (se	mended and are the basis of this report see Rule 70.16 and Section 607 of the		
		sheets which superse	de earlier sheets, but w	nich this Authority cons	iders contain an amendment that goes		
	. –	Supplemental Box.			cated in item 4 of Box No. I and the		
	b. (sent to the International Bureau only) a total of (indicate type and number of electronic carrier(s)), containing a sequence listing and/or tables related thereto, in computer readable form only, as indicated in the Supplemental						
	E	Box Relating to Sequence	Listing (see Section 80	2 of the Administrative	Instructions).		
4.	This report contains indications relating to the following items:						
	⊠ Box		-				
	_	No. II Priority	MON				
	_	· · · · · · · · · · · · · · · · · · ·	nent of opinion with rega	rd to novelty inventive	step and industrial applicability		
	_	No. IV Lack of unity of		id to novely, inventive	step and industrial applicability		
	⊠ Вох	No. V Reasoned state		2) with regard to novelty	r, inventive step or industrial		
	□ Вох	No. VI Certain docum		oupporting odon otator			
	□ Вох	No. VII Certain defects	in the international app	lication			
	□ Вох	No. VIII Certain observ	• •				
Date	of submis	sion of the demand		Date of completion of th	is report		
18.02.2005							
10.02.2000				03.11.2005			
Name and mailing address of the International				Authorized Officer			
preliminary examining authority: European Patent Office - Gitschiner Str. 103					The state of Land of the state		
		0-10958 Berlin Fel. +49 30 25901 - 0		Figiel, B	· 114 0)))		
-		Fax: +49 30 25901 - 840		Telephone No. +49 30 2	25901-473		
ł				l	41Mn		

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No. PCT/EP2004/008574

	Box No. I Basis of the repor	t			
1.	ith regard to the language , this report is based on the international application in the language in which it was				
	which is the language of a t international search (und publication of the internation	islations from the original language into the following language, translation furnished for the purposes of: der Rules 12.3 and 23.1(b)) ational application (under Rule 12.4) examination (under Rules 55.2 and/or 55.3)			
2.	With regard to the elements* of have been furnished to the recereport as "originally filed" and an	f the international application, this report is based on (replacement sheets which eiving Office in response to an invitation under Article 14 are referred to in this re not annexed to this report):			
	Description, Pages				
	2-9	as originally filed			
	1, 1a	received on 27.04.2005 with letter of 26.04.2005			
	Claims, Numbers				
	1-11	received on 27.04.2005 with letter of 26.04.2005			
	Drawings, Sheets				
	1/2, 2/2	as originally filed			
	☐ a sequence listing and/or a	ny related table(s) - see Supplemental Box Relating to Sequence Listing			
3.	☐ The amendments have res☐ the description, pages☐ the claims, Nos.☐ the drawings, sheets/fig☐ the sequence listing (sp☐ any table(s) related to s	pecify):			
4.	☐ This report has been estable had not been made, since they Supplemental Box (Rule 70.2(c) ☐ the description, pages ☐ the claims, Nos. ☐ the drawings, sheets/fig ☐ the sequence listing (sp. ☐ any table(s) related to s	s pecify):			
	* If item 4 applies, s	ome or all of these sheets may be marked "superseded."			

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No. PCT/EP2004/008574

Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N) Yes: Claims 1-11

No: Claims

Inventive step (IS) Yes: Claims 1-11

No: Claims

Industrial applicability (IA) Yes: Claims 1-11

No: Claims

2. Citations and explanations (Rule 70.7):

see separate sheet

Reasoned statement under Rule 43bis.1(a)(i)

- 1. It is considered that independent claims 1 (method) and 9 (system) relate to new and inventive subject-matter (Articles 33(2) and (3) PCT), since the prior art does not disclose or suggest the specifically claimed transparent access authentication of subscribers.
- 1.1 The following document

D1: "Access security for IP-based services (Release 5)" 3GPP TS 33.203 V5.6.0, June 2003 (2003-06), pages 1-27,34, XP002264085 (acknowledged in the description),

is regarded as being the closest prior art and discloses a method for access authentication of subscribers (Authentication of an IM-subscriber; paragraph 6.1.1) connected to an authenticating network domain by a GPRS core network or an UMTS network (PS-Domain in figure 1; also figure 3), wherein the method using data which are assembled by a network layer during establishment of a PDP context in GPRS networks (IP address established during establishment of a primary PDP context is *used* for all further communication; this feature is disclosed implicit in document D1).

- 1.2 The problem with this prior art is that no authentication on application layer is foreseen in GPRS standard. Thus there is the need to provide a transparent access authentication of subscribers without requiring extensions on network or client side (description, page 1, lines 25-29 and page 2, lines 15-16).
- 1.3 The application solves this problem by providing the method with following steps:
 - when a Gateway GPRS Support Node (1) receives a context creation request it queries a registration server (2) to get an IP address assigned for the particular PDP context, and within the context the registration server (2) receives a Mobile Station ISDN Number, MSISDN, and/or an International Mobile Subscriber Identity, IMSI, of the subscriber and stores for each PDP context a pair of IP address and IMSI/MSISDN in a session database (3),

- a proxy server (5) is provided which checks IMSI/MSISDN from a registration server (2) session database (3) and IMSI/MSISDN from a application domain database (4) for match,
- if the IMSI/MSISDN pairs are matching, the proxy server (5) checks a subscribers IP address assigned in the IP network layer for match with the IP address assigned by the registration server (2), and
- the proxy server (5) parses the application layer for IP addresses given in the headers of registration messages and checks for match with the network layer IP address which was already checked for match with the IP address assigned by the registration server (2).

No prior art document anticipates the proposed solution.

- 1.4 Independent **claim 9** contains the corresponding features as the method of claim 1 expressed respectively in terms of the system. The argumentation of the points 1.1-1.3 applies mutatis mutandis also for this claim.
- 2. Claims 2-4 and 6-11 are dependent respectively on claims 1 and 9 and therefore also meet the requirements of Art.33(2) and Art.33(3) PCT.

T03018 PCT

1

Transparent Access Authentication in 2G and 2.5G Mobile Access Networks

EPO - DG 1

28. 04. 2005

- The present invention relates to a method and system for transparent access authentication in 2G and 2.5G Mobile

 Access Networks. This includes communication networks of the GSM-, GPRS- and UMTS-standard well known to skilled persons.
- In standardisation of Universal Mobile Telecommunication
 System (UMTS Rel.5) comprehensive means are foreseen to
 perform authentication on the application layer with no need
 to interwork with the underlying radio and transport
 networks. The mechanisms are based on the assumption that a

 15 specific environment is prepared for deployment of IP
 Multimedia Subsystem (IMS) services. It includes the use of
 IMS SIM (ISIM) application, which in turn requires
 Rel.99UICC's in the connected end devices to handle the
 authentication and key agreement (AKA).
- In case of deployment of IMS and IMS based services in a network environment which is characterised by the use of SIM cards, the standardised authentication mechanism will not be applicable.
- 25 The Technical Specification 3GPP TS 33.203: "Access Security for IP-based Services", Release 5, V5.6.0, June 2003, XP-002264085, discloses a method for transparent access authentication of subscribers connected to an authenticating network domain by a GPRS core network or an UMTS network, the method using data which are assembled by a network layer during establishment of a PDP context in GPRS networks.

T03018 PCT

1a

It is the object of the invention to provide method and system for transparent access authentication which allow it to run authentication transparently to the end device, without requiring proprietary extensions and functions on network or client side.

This object is achieved by providing a method and system as described in the independent claims.

5

25

30

T03018 PCT

10

EPO-DG 1
28. 04. 2005

Claims

- 1. Method for transparent access authentication of subscribers connected to an authenticating network domain by a GPRS core network or an UMTS network, wherein the method using data which are assembled by a network layer during establishment of a PDP context in GPRS networks, characterised in
- that when a Gateway GPRS Support Node (1) receives a context creation request it queries a registration server (2) to get an IP address assigned for the particular PDP context, and within the context the registration server (2) receives a Mobile Station ISDN Number, MSISDN, and/or an International Mobile Subscriber Identity, IMSI, of the subscriber and stores for each PDP context a pair of IP address and IMSI/MSISDN in a session database (3), that a proxy server (5) is provided which checks IMSI/MSISDN from a registration server (2) session database (3) and IMSI/MSISDN from a application domain database (4) for match,

that if the IMSI/MSISDN pairs are matching, the proxy server (5) checks a subscribers IP address assigned in the IP network layer for match with the IP address assigned by the registration server (2), and that the proxy server (5) parses the application layer for IP addresses given in the headers of registration messages and checks for match with the network layer IP address which was already checked for match with the IP address assigned by the radius server (2).

2. Method according to claim 1, comprising the step that during PDP context establishment a Serving GPRS Support

15

20

30

T03018 PCT

11

Node (SGSN) is authenticating the subscriber using the A3/A8 algorithm based on an end devices SIM card.

- 3. Method according to any preceding claim, comprising the step that in all subsequent messages arriving at the proxy server (5), it checks for match of IP address in the IP packet overhead field for source address with that in the application layer protocol header fields and verifies the matching pairs against the IP address assigned by the Radius server (2).
 - 4. Method according to any preceding claim, that a routing module (7) is provided which is a standard entry point for all messages and decides by evaluation of Private ID, PrivID, which network node will handle the message.
 - 5. System of units in a mobile telecommunication network, characterised that at least a first authentication unit (2) is connected via a data line to a second unit (5; 6) which assembles data according to the method of claim 1.
 - 6. System according to claim 5, wherein the first unit comprises a registration server (2).
- 7. System according to claim 5 or 6, wherein the first unit (2) is connected to a session database (3).
 - 8. System according to any of claims 5 to 7, wherein the second unit comprises a proxy server (5).
 - 9. System according to any of claims 5 to 8, wherein the second unit comprises a Proxy Call State Control Function (6).

T03018 PCT

12

10. System according to any of claims 5 to 9, wherein the second unit (5; 6) is connected to a subscriber database (4).

5

11. System according to any of claims 5 to 10, wherein a routing module (7) is provided which decides by evaluation of Private ID, PivID, which network node will handle the message.

10